

EP 0 556 705 A1

19  European Patent office

11 Publication number: 0 556 705 A1

12 **EUROPEAN PATENT APPLICATION**

21 Application number: 93102074.7

51 International Classification: A61B 17/39

22 Application date: 02/10/93

43 Priority: 02/20/92 DE 4205213

43 Publication date of the application:  
08/25/93 Patent sheet 93/34

84 Known application countries:  
DE FR GB IT

71 Applicant: DELMA ELEKTRO UND  
MEDIZINISCHE APPARATEBAU  
GESELLSCHAFT, GmbH  
[DELMA ELEKTRO AND MEDICAL DEVICE  
PRODUCTION CORPORATION, LLC]  
Ludwigstaler Strasse 17-27  
D-78532 Tuttlingen, Germany

72 Inventor: Dornhof, Konstantin  
Bismarckstrasse 89  
W-7208 Spaichingen, Germany

74 Representative: Morgan, James G. et al  
Certified Physicist, Dr. Manitz,  
Dr. Finsterwald, Certified Profession  
Engineer, Certified Physicist Rotermond.  
Certified Chemist, Dr. Heyn, B. Sc.  
(Physicist) Morgan, Postfach 22 16 11, D-  
80506, Munich, Germany

#### 54 High-frequency surgical instrument

57 A high-frequency surgical instrument includes a high-frequency generator (13) loading two adjustable electrodes (11, 12) that are applicable to patient tissue, said generator possessing a current source (14) adjustable with respect to its power output and an oscillator (15) powered by it that includes an output end stage, and produces a specific power output depending on the adjustment of the current source (14) and the electrical resistance (R) of the tissue between the electrodes (11, 12). A number of specified curves is stored in a digital buffer (19) that are representative of a specific functional dependence between the power output of the high-frequency generator (13) and the electrical resistance (R) of the tissue, and that take into account the characteristic curves of the high-frequency generator (13). A control address is stored at a control unit (21) connected with the digital buffer (19) corresponding to the actual electrical resistance (R) of the tissue and to the selected operating mode.

